

KEMET Part Number: ALC80A561EF450
(A547HH561M450A)

ALC80, Aluminum Electrolytic, 560 uF, 20%, 450 VDC, -40/+105°C



General Information	
Series:	ALC80
Dielectric:	Aluminum Electrolytic
Description:	Snap-In, Aluminum Electrolytic
RoHS:	Yes
Lead:	2 Pin
AEC-Q200:	No
Halogen Free:	Yes
Notes:	Dimensions D And L Include Slewing.
Shelf Life:	156 Weeks

Dimensions	
D	40mm +1mm
L	50mm +/-2mm
S	10mm +/-0.1mm
LL	6.3mm +/-1mm
F	2mm +/-0.1mm

Specifications	
Capacitance:	560 uF
Capacitance Tolerance:	20%
Voltage DC:	450 VDC, 495 VDC (Surge)
Temperature Range:	-40/+105°C
Rated Temperature:	105°C
Life:	9000 Hrs (Rated Voltage And Ripple Current At 105C), 14000 Hrs (Rated Voltage at 105C)
Resistance:	240 mOhms (100Hz 20C), 139.7 mOhms (10kHz 20C)
Ripple Current:	3.2 Amps (100Hz 105C), 7.969 Amps (10kHz 105C)
Leakage Current:	756 uA (5min 20°C)

Packaging Specifications	
Weight:	105 g
Slewing:	Yes
Packaging:	Bulk, Bag