


T555, Tantalum, Polymer Tantalum, HRA, 100 uF, 20%, 50 VDC, N/A, 130 mOhms, Height Max = 9.6mm



General Information	
Series:	T555
Dielectric:	Polymer Tantalum
Style:	SMD Chip
RoHS:	No
Termination:	Tin
AEC-Q200:	No
Component Weight:	5.54 g
Shelf Life:	156 Weeks

Dimensions	
L	24.5mm +/-0.5mm
W	8.5mm +/-0.5mm
H	9.1mm +/-0.5mm
S	3mm +/-0.3mm
F	4.2mm +/-0.5mm

Packaging Specifications	
Packaging:	Bulk, Box
Packaging Quantity:	100

Specifications	
Capacitance:	100 uF
Capacitance Tolerance:	20%
Voltage DC:	50 VDC, 39 VDC (105°C), 57.5 VDC (85°C)
Temperature Range:	-55/+105°C
Dissipation Factor:	5% (120Hz 25C)
Failure Rate:	N/A
Resistance:	130 mOhm (100kHz 25C)
Ripple Current:	1450 mAmps (40kHz 85C)
Leakage Current:	37.5 uA (5min 25°C)
Testing and Reliability:	25C +/-5C, 10 Cycles, After Constant Voltage Conditioning (KEMET Standard)